Certificate of Compliance

Certificate Number:
S7256

Report Reference:
S7256-20260914

Issue Date:
2026-09-18

Issued to:

Pfannenberg GmbH
Werner-Witt-Strasse 1
Hamburg 21035 Germany

This certificate confirms that representative samples of:

AUDIBLE-SIGNAL APPLIANCES, GENERAL SIGNAL

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

UL 464A, Audible Signal Appliances for General Signaling Use, Edition 1, Revision Date 03/24/2021

UL 1638A, Visual Signal Appliances for General Signaling Use, Edition 1, Revision Date 09/21/2021.

CSA C22.2 No. 205, Signal Equipment, Edition 3, Revision Date 05/2020.

Additional Information:
See UL Product iQ® at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2026 UL LLC. All rights reserved.

CERTIFICATE OF COMPLIANCE

Certificate number	S7256
Report reference	S7256-20260914
Date	2026-09-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

General Signaling Equipment:

USL1, CNL1: Horn/Strobe Model PA L 1-R xx yy zz can be rated: 12-48VDC, 24-48VAC, 115-230VAC

USL2, CNL1: Horn Model PA 1-R xx zz can be rated: 12-48VDC, 24-48VAC, 115-230VAC

Where:

xx = Voltage Ranges Above

yy = Lens Color: -CL/AM/RD/YE/BU/GR/RGB

zz = Housing Color: 3000 (flame red) or 7035 (light grey)

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2026 UL LLC. All rights reserved.